

## Declaration of Performance

DOP no.: TP15006-02

- |   |   |
|---|---|
| 1. Unique identification code of the product-type:  | Steel sections for system walls (Refer point 8)   |
| 2. Intended use of the product:   | Interior system walls   |
| 3. Manufacturer:  | Triplan International A/S<br>Industriskellet 12-16<br>DK-2635 Ishøj, Denmark  |
| 4. Legal representative:  | N/A   |
| 5. System of assessment and verification of constancy of performance of the construction product: | System 4  |
| 6. Assessment:  | Identification of the type based on type testing and the factory's own production control system (FPC) in accordance with the requirements of EN 14353+A1:2010 according to System 4, is carried out by the manufacturer. |
| 7. Declared performance:  | Refer point 8   |
| 8. Technical documentation:   | Refer table.  |

| Essential characteristics: | Declaration of Performance:   |   |  |   |  | Harmonized technical specifications: |
|----------------------------|---|---|--|---|--|--------------------------------------|
|                            | Omega-F-section-<br>Abutment<br>Steel cap<br>Aspira-<br>Asymmetrical- | Track<br>Head track<br>Base list<br>Cover cap<br>Horizontal<br>frame<br>Side frame<br>Blind door<br>frame | H-section<br>Single H-section<br>Groove section<br>U-channel<br>45°<br>90° | Bottom trim<br>Top trim<br>U-Top trim<br>TVO<br>TF<br>TFL<br>TF/TFL | TP Lite III<br>TC Lite<br>Steel shelf<br>Accessories |                                      |
| Reaction to fire (R2F):    | A1  | A1  | A1   | A1  | A1   | EN 14353+A1:2010                     |
| Flexural strength (F):     | 250 N/mm <sup>2</sup>   | 250 N/mm <sup>2</sup>   | 250 N/mm <sup>2</sup>  | 250 N/mm <sup>2</sup>   | 250 N/mm <sup>2</sup>                                | EN 14353+A1:2010                     |
| Dangerous substances:      | NPD   | NPD   | NPD  | NPD   | NPD  | EN 14353+A1:2010                     |

N/A – Not Applicable

NPD – No Performance Determined

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ishøj  
April 26th 2016

Signature:   
Klaus Groth Larsen, Managing Director